

Asphalt Primer - Black

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : Asphalt Primer - Black

Manufacturer or supplier's details

Company : Johns Manville
 Address : P.O. Box 5108
 Denver, CO USA 80127

Telephone : 303-978-2000 8:00AM-5:00PM M-F
 Emergency telephone number : 1-800-424-9300 (Chemtrec, in English)

Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Carcinogenicity : Category 1B

Aspiration hazard : Category 1

GHS Label element

Hazard pictograms :




Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H350 May cause cancer.

Precautionary statements : **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P280 Wear protective gloves/ eye protection/ face protection.
Response:
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off

Asphalt Primer - Black

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

immediately all contaminated clothing. Rinse skin with water/ shower.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
asphalt	8052-42-4	>= 50 - < 70
Stoddard solvent	8052-41-3	>= 30 - < 50
Asphalt, oxidized	64742-93-4	>= 10 - < 20

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Symptoms of poisoning may appear several hours later.
 Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
 If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.
 Immediately flush eye(s) with plenty of water.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
 Do NOT induce vomiting.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
 Take victim immediately to hospital.

Asphalt Primer - Black

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.

Asphalt Primer - Black

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharges.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Open drum carefully as content may be under pressure.
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
 Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
asphalt	8052-42-4	TWA (Fume, inhalable fraction)	0.5 mg/m ³ (as benzene soluble aerosol)	ACGIH
		C (Fumes)	5 mg/m ³	NIOSH REL
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m ³	NIOSH REL
		C	1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,900 mg/m ³	OSHA
		TWA	100 ppm 525 mg/m ³	OSHA

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection
 Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Eye protection : Tightly fitting safety goggles

Skin and body protection : impervious clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Asphalt Primer - Black

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
Written instructions for handling must be available at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : dark

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available
: 149 - 260 °C

Flash point : 40 °C

Evaporation rate : 0.2

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 3 hPa

Relative vapour density : No data available

Relative density : 0.88 - 0.99

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Thermal decomposition : No data available

Viscosity, dynamic : No data available

Asphalt Primer - Black

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

Viscosity, kinematic : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

SECTION 11. TOXICOLOGICAL INFORMATION**IARC** Group 2A: Probably carcinogenic to humans

Asphalt, oxidized 64742-93-4

ACGIH No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.**OSHA** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.**Further information****Product:**

Remarks: Solvents may degrease the skin.

Components:**asphalt:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Asphalt Primer - Black

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

Components:**asphalt:**

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**Disposal of residual product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.**SECTION 14. TRANSPORT INFORMATION****International transport regulations**

Exempt, Combustible Liquid per 49 CFR 173.150.

SECTION 15. REGULATORY INFORMATIONTSCA list : Not relevant
Not relevant**EPCRA - Emergency Planning and Community Right-to-Know Act**

Asphalt Primer - Black

Version 1.2

Revision Date 05/29/2015

Print Date 05/29/2015

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

California Prop 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

SECTION 16. OTHER INFORMATION**Further information**

Revision Date : 05/29/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.