

Asphalt Roll Roofing Products

Version 1.6

Revision Date 09/30/2015

Print Date 09/30/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : GlasPly® IV, GlasPly® Premier

Manufacturer or supplier's details

Company : Johns Manville
Address : P.O. Box 5108
Denver, CO USA 80127

Telephone : 303-978-2000 8:00AM-5:00PM M-F
Emergency telephone number : 1-800-424-9300 (Chemtrec, in English)

Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Carcinogenicity : Category 1B

GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H350 May cause cancer.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Asphalt Roll Roofing Products

Version 1.6

Revision Date 09/30/2015

Print Date 09/30/2015

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
Oxidized Asphalt	Not Assigned	>= 30 - < 50
limestone	1317-65-3	>= 10 - < 20
Talc (Mg3H2(SiO3)4)	14807-96-6	>= 5 - < 10

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Immediately flush eye(s) with plenty of water.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : None known.

SECTION 5. FIREFIGHTING MEASURES

- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and : Use personal protective equipment.
Avoid dust formation.

Asphalt Roll Roofing Products

Version 1.6

Revision Date 09/30/2015

Print Date 09/30/2015

- emergency procedures : Avoid breathing dust.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
limestone	1317-65-3	TWA (total dust)	15 mg/m ³	OSHA
		TWA (Total dust)	15 mg/m ³	OSHA
		TWA (respirable dust fraction)	5 mg/m ³	OSHA
		TWA (respirable fraction)	5 mg/m ³	OSHA
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA
		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA	0.1 fibre/cm ³	ACGIH
		TWA	2 mg/m ³	ACGIH

Asphalt Roll Roofing Products

Version 1.6

Revision Date 09/30/2015

Print Date 09/30/2015

		(Respirable fraction)		
		TWA (respirable dust fraction)	2 mg/m ³	OSHA

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.
Dust safety masks are recommended when the dust concentration is more than 10 mg/m³.

Hand protection

Remarks : For prolonged or repeated contact use protective gloves.

Eye protection : Safety glasses

Skin and body protection : If used and stored as directed, no special protective equipment is necessary.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
Written instructions for handling must be available at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : MAT

Colour : dark brown

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/range : 95 °C

Boiling point/boiling range : 300 °C

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Asphalt Roll Roofing Products

Version 1.6

Revision Date 09/30/2015

Print Date 09/30/2015

Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Components:****limestone:**

Acute oral toxicity : LD50 (Rat): > 6,450 mg/kg

IARC

Group 2A: Probably carcinogenic to humans

Oxidized Asphalt

ACGIH

Confirmed human carcinogen

Talc (Mg₃H₂(SiO₃)₄)

14807-96-6

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

Known to be human carcinogen

Asphalt Roll Roofing Products

Version 1.6

Revision Date 09/30/2015

Print Date 09/30/2015

Talc (Mg₃H₂(SiO₃)₄)

14807-96-6

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: Warning: Manufactured with /\$, a substance which
harms public health and environment by destroying ozone in
the upper atmosphere.

Additional ecological information : No data available

Components:**Oxidized Asphalt:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Disposal of residual product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.

Asphalt Roll Roofing Products

Version 1.6

Revision Date 09/30/2015

Print Date 09/30/2015

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

These products are not classified as dangerous goods according to international transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

TSCA - 5(a) Significant New Use Rule List of Chemicals : Oxidized Asphalt

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D) : Not relevant

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
formaldehyde	50-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
formaldehyde	50-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 : The following components are subject to reporting levels established by SARA Title III, Section 302:

Oxidized Asphalt Not Assigned 45 %

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion Potential :

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

Asphalt Roll Roofing Products

Version 1.6

Revision Date 09/30/2015

Print Date 09/30/2015

The following chemical(s) are listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F):

Oxidized Asphalt	Not Assigned	45 %
------------------	--------------	------

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Oxidized Asphalt	Not Assigned	45 %
------------------	--------------	------

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6
formaldehyde	50-00-0

The components of this product are reported in the following inventories:

TSCA : Listed on TSCA

DSL : This product contains one or several components listed in the Canadian NDSL.

SECTION 16. OTHER INFORMATION**Further information**

Revision Date : 09/30/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.