

**JM Single Ply Caulk**

Version 1.5

Revision Date 11/15/2016

Print Date 11/15/2016

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Trade name : JM Single Ply Caulk

Manufacturer or supplier's details

Company : Johns Manville  
Address : P.O. Box 5108  
Denver, CO USA 80127

Telephone : +1 303-978-2000 8:00AM-5:00PM M-F  
Emergency telephone number : 1-800-424-9300 (Chemtrec, in English)

Prepared by : productsafety@jm.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Carcinogenicity : Category 2

Flammable solids : Category 1

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2A

**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H228 Flammable solid.  
H350 May cause cancer.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.

Precautionary statements :

**Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ eye protection/ face protection.  
P264 Wash skin thoroughly after handling.

**Response:**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## JM Single Ply Caulk

Version 1.5

Revision Date 11/15/2016

Print Date 11/15/2016

P337 + P313 If eye irritation persists: Get medical advice/attention.  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P332 + P313 If skin irritation occurs: Get medical advice/attention.  
 P362 Take off contaminated clothing and wash before reuse.  
 P308 + P313 IF exposed or concerned: Get medical advice/attention.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**
**Hazardous components**

Chemical name	CAS-No.	Concentration (%)
limestone	1317-65-3	>= 20 - < 30
Solvent naphtha (petroleum), light aliph.	64742-89-8	>= 20 - < 30
titanium dioxide	13463-67-7	>= 5 - < 10
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 1 - < 5
calcium oxide	1305-78-8	>= 1 - < 5
silicon, amorphous	112945-52-5	>= 1 - < 5

---

**SECTION 4. FIRST AID MEASURES**

- General advice** : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Symptoms of poisoning may appear several hours later.  
 Do not leave the victim unattended.
- If inhaled** : Consult a physician after significant exposure.  
 If unconscious place in recovery position and seek medical advice.
- In case of skin contact** : If skin irritation persists, call a physician.  
 If on skin, rinse well with water.  
 If on clothes, remove clothes.
- In case of eye contact** : Remove contact lenses.  
 Immediately flush eye(s) with plenty of water.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.
- If swallowed** : Keep respiratory tract clear.

**JM Single Ply Caulk**

Version 1.5

Revision Date 11/15/2016

Print Date 11/15/2016

Do NOT induce vomiting.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

Most important symptoms  
and effects, both acute and  
delayed : None known.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for : Contain spillage, and then collect with non-combustible

## JM Single Ply Caulk

Version 1.5

Revision Date 11/15/2016

Print Date 11/15/2016

containment and cleaning up

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
limestone	1317-65-3	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA
		TWA (Total dust)	15 mg/m <sup>3</sup>	OSHA
		TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	OSHA
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA
Solvent naphtha (petroleum), light aliph.	64742-89-8	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA

**JM Single Ply Caulk**

Version 1.5

Revision Date 11/15/2016

Print Date 11/15/2016

		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA
titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA
		TWA (Total dust)	10 mg/m <sup>3</sup>	OSHA
		TWA	10 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
calcium oxide	1305-78-8	TWA	2 mg/m <sup>3</sup>	ACGIH
		TWA	2 mg/m <sup>3</sup>	NIOSH REL
		TWA	5 mg/m <sup>3</sup>	OSHA
		TWA	5 mg/m <sup>3</sup>	OSHA
silicon, amorphous	112945-52-5	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA
		TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)	OSHA
		TWA	6 mg/m <sup>3</sup> (Silica)	NIOSH REL

**Personal protective equipment**

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
- Eye protection : Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.  
Written instructions for handling must be available at the work place.

**JM Single Ply Caulk**

Version 1.5

Revision Date 11/15/2016

Print Date 11/15/2016

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: solid
Colour	: white
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Boiling point/boiling range	: 104 °C
Flash point	: 18 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6.7 %(V)
Lower explosion limit	: 0.9 %(V)
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.

**JM Single Ply Caulk**

Version 1.5

Revision Date 11/15/2016

Print Date 11/15/2016

Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Hazardous decomposition products	:	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute inhalation toxicity	:	Acute toxicity estimate : 17000 ppm Exposure time: 4 h Test atmosphere: gas Method: Calculation method
---------------------------	---	---

**Acute toxicity****Components:****limestone:**

Acute oral toxicity	:	LD50 (Rat): > 6,450 mg/kg
---------------------	---	---------------------------

**Acute toxicity****Solvent naphtha (petroleum), light aliph.:**

Acute oral toxicity	:	LD50 (Rat): > 8,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 3400 ppm Exposure time: 4 h
Acute dermal toxicity	:	LD50 (Rat): > 4,000 mg/kg

**Acute toxicity****titanium dioxide:**

Acute inhalation toxicity	:	LC50 (Rat): 6,820 mg/m <sup>3</sup> Exposure time: 4 h
---------------------------	---	---

**Acute toxicity****calcium oxide:**

Acute oral toxicity	:	No data available :
Acute inhalation toxicity	:	No data available :
Acute dermal toxicity	:	No data available :

**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation and/or dermatitis.

**JM Single Ply Caulk**

Version 1.5

Revision Date 11/15/2016

Print Date 11/15/2016

**Serious eye damage/eye irritation****Product:**

Remarks: May cause irreversible eye damage.

**Germ cell mutagenicity****Components:****Solvent naphtha (petroleum), light aliph.:**

Germ cell mutagenicity- Assessment : In vivo tests showed mutagenic effects

**Carcinogenicity****Components:****Solvent naphtha (petroleum), light aliph.:**

Carcinogenicity - Assessment : Possible human carcinogen

**IARC**

Group 2B: Possibly carcinogenic to humans

titanium dioxide

13463-67-7

**ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Aspiration toxicity****Components:****Solvent naphtha (petroleum), light aliph.:**

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks: Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available



**JM Single Ply Caulk**

Version 1.5

Revision Date 11/15/2016

Print Date 11/15/2016

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

Additional ecological : No data available  
information

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Disposal of residual product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION****International transport regulations**

DOT Shipping Name: UN1325, Flammable solids, organic, n.o.s. (solvent naphtha), 4.1, PG II, ERG  
133

May be reclassified as "Consumer commodity, ORM-D" when shipped by ground in the US in inner  
packagings not over 1.0 kg (2.2 pounds) net capacity each, packed in a strong outer packaging.

---

**SECTION 15. REGULATORY INFORMATION****TSCA list**

TSCA - 5(a) Significant New Use Rule List of : Not relevant  
Chemicals

US. Toxic Substances Control Act (TSCA) Section : Not relevant  
12(b) Export Notification (40 CFR 707, Subpt D)

**JM Single Ply Caulk**

Version 1.5

Revision Date 11/15/2016

Print Date 11/15/2016

**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

**California Prop 65**

WARNING! This product contains a chemical known to the State of California to cause cancer.

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
quartz (SiO <sub>2</sub> )	14808-60-7
titanium dioxide	13463-67-7

**The components of this product are reported in the following inventories:**

TSCA : On TSCA Inventory

DSL : This product contains the following components listed on the Canadian NDSL. All other components are on the Canadian DSL.

: limestone

**SECTION 16. OTHER INFORMATION****Further information**

Revision Date : 11/15/2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.